

AMC100 | 100 mm Manual Analytical Probe Station For True DC/CV and RF measurements

FEATURES / BENEFITS

- ✚ *Manual stage assembly with up to 100mm x 100mm range of motion*
- ✚ *Powder-coated steel platen holds up to 10 magnetic or vacuum-based positioners.*
- ✚ *High quality stereo zoom/compound microscopes with high-intensity LED lighting provide outstanding vision at magnifications. Includes camera port*
- ✚ *Standard boom/bridge mounts assembly for full-range XYZ positioning of microscope. XY range of 25mm x25mm (higher range available).*
- ✚ *Available high resolution micropositioners*
- ✚ *Compatible for the temperature Range:-70°C to 200°C*
- ✚ *RF options available (Up to 67 GHz) include customizable RF probes, RF bias-able chuck, and shielding enclosures*



SPECIFICATIONS

Chuck XYZ Stage Travel:

Total travel range	: Up to 100 mm x 100 mm
Travel resolution	: < 1.0 μm
Planarity	: ≤ 10 μm, Optional available on request
Chuck Z axis adjustment	: 10 mm

Chuck Theta travel	: $\pm 5^\circ$
Chuck Pull Out Stage	: pull out Stage

PLATEN:

Specifications:

Material	: Stainless Steel
Chuck to platen height	: Min. 10 mm
Platen lift control	: Fixed, Platen lift of up 20 mm available on request(Optional)
Max. No of Micro-Positioners	: Up to 6 DC and 4 RF Positioners
Micropositioners Mounting	: Compatible for both Magnetic as well as Vacuum base micropositioners
RF Micro-Positioner mounting	: Magnetic/Vacuum base with guided rail
DC Micro-Positioner mounting	: Magnetic/Vacuum base

NON-THERMAL CHUCKS

Standard Wafer Chuck:

Chuck Connections	: Coaxial(BNC)/ Triaxial
Chuck Diameter	: Up to 100 mm
Chuck Material	: Stainless Steel. Chuck made of other material is available as optional
Chuck surface	: Planar with centric engraved vacuum grooves
Chuck Sample actuation	: Vacuum actuation with three zone vacuum holes
Sample Size	: Min 5mm x 5mm up to 100 mm wafer
Chuck Surface Planarity	: 10 μ m, Optional down to $\pm 3\mu$ m

RF Wafer Chuck:

Chuck Connections	: Coaxial(BNC)
Chuck Diameter	: Up to 100 mm 2 AUX chuck as optional
Chuck Material	: Nickel Plated aluminum, Ceramic etc
Chuck surface	: Planar with centric engraved vacuum grooves
Chuck Sample actuation	: Vacuum actuation with three zone vacuum holes
Sample Size	: Min 5mm x 5mm up to 100 mm wafer
Chuck Surface Planarity	: 10 μ m, Optional down to $\pm 3\mu$ m

Auxiliary Chuck:

Quantity	: 2 Nos of AUX Chuck
Chuck Diameter	: Up to 100 mm
Chuck Material	: Derlin, Ceramic, RF absorbing material
Chuck Sample actuation	: Separate vacuum control switches for auxiliary chucks
Sample Size	: Min 5mm x 5mm up to 150 mm wafer
Chuck Surface Planarity	: 10 μ m, Optional down to \pm 3 μ m

ELECTRICAL SPECIFICATIONS:

Standard Chuck @10 V:

Parameter	Coaxial Chuck	Triaxial Chuck
Maximum voltage between chuck and GND	500 V DC	500 V DC
Isolation	> 2 G Ω	Force to guard > 25T Ω Guard to shield > 3T Force to shield > 500G Ω
Leakage current	< 50pA	\leq 50fA
Capacitance	< 800pF	< 100fF
Chuck Flatness	\leq 10 μ m	\leq 10 μ m

HOT and COLD CHUCK:

Parameter	Coaxial Chuck	Triaxial Chuck
Temperature Control Method	Peltier Type	Peltier Type
Temperature Range	-70 $^{\circ}$ C - 200 $^{\circ}$ C	-70 $^{\circ}$ C - 200 $^{\circ}$ C,
Temperature Accuracy	\pm 0.5 $^{\circ}$ C	\pm 0.5 $^{\circ}$ C
Temperature Stability	\pm 1 $^{\circ}$ C	\pm 1 $^{\circ}$ C
Connection Interface	RS232/RS484	RS232/RS485
Chuck Surface Plating	Copper plated with Nickel/Gold	Copper Plated with Nickel/Gold
Leakage Current	< 100pA	<100fA

Micropositioners:

Model	Description
-------	-------------

MH100	Fixed Magnet Base Switchable Magnet Base Vacuum Base	
MH100	Foot dimension	70 x 50mm
	Travel range X,Y	12mm
	Travel range Z	8mm
	Feature Resolution	1µm/0.8µm
	TPI resolution	80 TPI/100TPI
MH300	Fixed Magnet Base Switchable Magnet Base Vacuum Base	
MH300	Foot dimension	70 x 35mm
	Travel range X,Y	12mm
	Travel range Z	12mm
	Feature Resolution	3µm
MH500	Switchable magnet base Vacuum Base	
MH500	Foot dimension	80 x 90mm
	Travel range X , Y	±15 mm
	Travel range Z	±15 mm
	Feature Resolution	3µm

✚ Probe Tip Holders with Connecting Cable:

Model	Description
Coaxial Tip Holder with Coaxial Cable	
SHC15	Spring Holder/1.5m coax cable/BNC male
THC15	Tube Holder/1.5m coax cable/BNC male
NHC15	Nut Holder/1.5m coax cable/BNC male
Triaxial Tip Holder with Triaxial Cable	
THT15	Tube Holder/1.5m Triax cable/Triax male
NHT15	Nut Holder/1.5m Triax cable/Triax male
High Frequency Probe Arms	
MWA-EW	HF probe arm (east-west)
MWA-NS	HF probe arm(north - south)

System Dimensions: 580mm wide x460mm deep x 245mm high

Weight: 42kg to 50kg depending on options selected